

D121014H11

EtherDAS™ Omni-Directional In-Building Antenna / 698-960, 1710-2500, 2501-2700 MHz / 2, 5, 5 dBi / 360°

In-building Omni

Frequency Range	698-960	1710-2500	2501-2700
------------------------	---------	-----------	-----------

Model No.	D121014H11		
------------------	-------------------	--	--

		698-960	1710-2500	2501-2700
Frequency Range	(MHz)	698-960	1710-2500	2501-2700
Gain	(dBi)	2	5	5
Azimuth Beam width	(°)	360	360	360
Elevation Beam width	(°)	80	65	65

VSWR		< 1.7:1	< 1.8:1	< 2.0:1
Polarization			Vertical	
Intermodulation IM3	(dBc)		< -153 (2x43 dBm carrier)	
Impedance	(Ω)		50	
Max. Effective Power per Port	(watts)		50	

Mechanical Specifications

Connector Type & Quantity		N Female x 1 (Cable Length : 452.12 mm / 17.8")
Connector Position		Top
Antenna Dimension (H x W x D)	(mm/in)	Ø202.5 x 102.1 Ø7.97 x 4.02
Weight (Clamp incl.)	(kg/lb)	0.52 1.14
Mounting		Ceiling mount
Radome (Color)		PC, UL94V-0 UV resistant
Product Environmental compliance		ROHS compliant



